


## ANTI-VIBRATION MOUNT KITS









## ANTI-VIBRATION MOUNT KITS

Suitable for domestic units, small pumps, generators, air conditioning units or heat pumps.

The colors identify the weight of the machine and inside each package you can find a kit of screws, washers and nuts and instructions for installation.

All *anti-vibration feet* are made of THERMOPLASTIC ELASTOMER which unlike natural rubber, has a high resistance to tearing, atmospheric aging, ozone, detergents, UV rays and also resists to temperatures from  $-45^{\circ}\text{C}$  to  $+110^{\circ}\text{C}$ .

Discover our modular COUNTER DISPLAY on page 25.




## HOW TO CHOOSE THE SUITABLE SERIES?


KIT SERIES	WEIGHT OF THE MACHINE TO ISOLATE						TYPE OF FIXING				SPRING INSIDE	INFO ON PAGE
	max. 120 Kgs	max. 170 Kgs	max. 450 Kgs	max. 600 Kgs	max. 1000 Kgs	max. 1600 Kgs	ON WALL BRACKET	ON GROUND BASE	GROUND ANCHORING	ON THE GROUND		
MNaZc series	●						●	●			●	3
PMNaZc series	●								●		●	5
MNaZb series		●					●	●			●	7
PMNaZb series		●							●		●	9
MNT series			●							●		11
NOCE4040 series			●				●	●				13
PNOCE4040 series			●						●			15
SEG9525 series				●					●	●		17
NOCE6050 series					●		●	●				19
PNOCE6050 series					●				●	●		21
MCF series						●				●		23

This chart shows the maximum weights achieved by the series.

To view the machine weights covered by the different kits within each series, view the pages indicated in the chart.



**SPRING INSIDE**



## MNaZc series

**WIND RESISTANT**

PATENTED telescopic anti-vibration spring mount that allows, once loaded, to increase the axial resistance to thrusts due to the action of the wind.


Suitable to isolate air conditioning units, pumps or fans.

### KIT CONTENTS

- 4 MNaZc feet
- 8 M8 washers
- 8 M8 TE screws
- Installation guide



**MNaZc**



max.  
55 Kgs

max.  
80 Kgs

max.  
120 Kgs



CB1MNaV/00000



CB1MNaG/00000





CB1MNaM/00000

**ON WALL BRACKET  
ON GROUND BASE**




## INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes considering that the stiffer feet must be installed on the opposite side of the grill, as indicated in the instructions contained inside the blister.
2. Fix the feet to the machine and to the bracket using screws and washers.
3. Anti-vibration feet installed correctly.



**SPRING INSIDE**



## PMNaZc series

### WIND RESISTANT

PATENTED telescopic anti-vibration spring mount that allows, once loaded, to increase the axial resistance to thrusts due to the action of the wind.

Steel base plate with 2 cavities for anchoring the mount to the ground.




The surface of the plates has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.



### KIT CONTENTS

- 4 PMNaZc feet
- 4 M8 washers
- 8 M8 TE screws
- Allen key and Installation guide

**PMNaZc**



max.  
55 Kgs



CB1PMNaV/00000

max.  
80 Kgs



CB1PMNaG/00000

max.  
120 Kgs




CB1PMNaM/00000


## GROUND ANCHORING



## INSTALLATION INSTRUCTIONS

1. Screw the plates to the colored bases of the anti-vibration feet with the screws and the allen wrench supplied.
2. Place the feet in correspondence of the anchoring holes considering that the stiffer feet must be installed on the opposite side of the grill, as indicated in the instructions contained inside the blister.
3. Fix the feet to the machine and to the bracket using screws and washers.





**SPRING INSIDE**



## MNaZb series

### WIND RESISTANT

PATENTED telescopic anti-vibration spring mount that allows, once loaded, to increase the axial resistance to thrusts due to the action of the wind.


Suitable to isolate air conditioning units, pumps or fans.

#### KIT CONTENTS

- 4 MNaZb feet
- 8 M8 washers
- 8 M8 TE screws
- Installation guide



**MNaZb**





max.  
90 Kgs

max.  
120 Kgs

max.  
170 Kgs



CB1MNaZbV/00000

CB1MNaZbG/00000



CB1MNaZbM/00000

**ON WALL BRACKET  
ON GROUND BASE**




## INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes considering that the stiffer feet must be installed on the opposite side of the grill, as indicated in the instructions contained inside the blister.
2. Fix the feet to the machine and to the bracket using screws and washers.
3. Anti-vibration feet installed correctly.



**SPRING INSIDE**



## PMNaZb series

### WIND RESISTANT

PATENTED telescopic anti-vibration spring mount that allows, once loaded, to increase the axial resistance to thrusts due to the action of the wind.

Steel base plate with 2 cavities for anchoring the mount to the ground.




The surface of the plates has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.



### KIT CONTENTS

- 4 PMNaZb feet
- 4 M8 washers
- 8 M8 TE screws
- Allen key and Installation guide

**PMNaZb**



max.  
90 Kgs



CB1PMNaZbV/00000

max.  
120 Kgs



CB1PMNaZbG/00000

max.  
170 Kgs





CB1PMNaZbM/00000

## GROUND ANCHORING



## INSTALLATION INSTRUCTIONS

1. Screw the plates to the colored bases of the anti-vibration feet with the screws and the allen wrench supplied.
2. Place the feet in correspondence of the anchoring holes considering that the stiffer feet must be installed on the opposite side of the grill, as indicated in the instructions contained inside the blister.
3. Fix the feet to the machine and to the bracket using screws and washers.



# MNT series




## ELASTOMERIC DAMPER

Damper in THERMOPLASTIC ELASTOMER which has a high resistance to tearing, atmospheric aging, ozone, detergents, UV rays and also resists to temperatures from -45°C to +110°C.

The surface of the plate and the base has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.

### KIT CONTENTS

- 4 MNT feet
- 4 M8 nuts (available also in M10)
- 4 M8 washers (available also in M10)
- Installation guide



max.  
150 Kgs



**CBMNTM8V2040L**

max.  
300 Kgs



**CBMNTM8V2040W**

max.  
450 Kgs





**CBMNTM8V2040M**


**ON THE  
GROUND**



## INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes.
2. Fix the feet to the machine using nuts and washers.
3. Anti-vibration feet installed correctly.





# NOCE4040 series

## DAMPER WITH CONTROLLED DEFLECTION

PATENTED elastomeric NOCE4040 series damper, designed with an elastic element defined as a connector which, when used between two containers, creates the condition to obtain anti-vibration devices with controlled deflection. This design prevents the vibration damper's deformation under load while insuring the perfect machine's insulation.




### AVAILABLE VERSIONS

Available in the following versions: nut-nut (NOCE4040DD), screw-nut (NOCE4040VD) or screw-screw (NOCE4040VV) depending on the anchoring needs.

### KIT CONTENTS


- 4 NOCE4040 feet
- M8 nuts
- M8 washers
- M8 TE screws
- Installation guide

NOCE4040DD




SCREWS: 8 M8 washers - 8 M8 TE screws

NOCE4040VD



SCREWS: 4 M8 nuts - 8 M8 washers - 4 M8 TE screws

NOCE4040VV



SCREWS: 4 M8 nuts - 8 M8 washers

max.  
100 Kgs

max.  
200 Kgs

max.  
350 Kgs

max.  
450 Kgs



CBNOCEVD4040L



CBNOCEVD4040W



CBNOCEVD4040M





CBNOCEVD4040H


**ON WALL BRACKET  
ON GROUND BASE**



## INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes.
2. Fix the feet to the machine and to the bracket using screws, nuts and washers depending on your necessity.
3. Anti-vibration feet installed correctly.





# PNOCE4040V series

## DAMPER WITH CONTROLLED DEFLECTION

PATENTED elastomeric *NOCE4040* series damper, designed with an elastic element defined as a connector which, when used between two containers, creates the condition to obtain anti-vibration devices with controlled deflection. This design prevents the vibration damper's deformation under load while insuring the perfect machine's insulation.




Steel base plate with 2 cavities for anchoring the mount to the ground. The surface of the plates has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.

### KIT CONTENTS

- 4 PNOCE4040V feet
- 4 M8 nuts
- 4 M8 washers
- Allen key and Installation guide



PNOCE4040V





max.  
100 Kgs



CBPNOCE4040V22M08L

max.  
200 Kgs



CBPNOCE4040V22M08W

max.  
350 Kgs



CBPNOCE4040V22M08M

max.  
450 Kgs



CBPNOCE4040V22M08H

## GROUND ANCHORING



## INSTALLATION INSTRUCTIONS

1. Screw the plates to the bases of the anti-vibration feet with the screws and the allen wrench supplied.
2. Place the feet in correspondence of the anchoring holes.
3. Fix the feet to the machine and to the bracket using screws, nuts and washers depending on your necessity.

1.



2.



3.



# SEG9525 series




## ELASTOMERIC DAMPER

Damper in THERMOPLASTIC ELASTOMER which has a high resistance to tearing, atmospheric aging, ozone, detergents, UV rays and also resists to temperatures from -45°C to +110°C.

The base has slip-proof flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise. The base has 2 slotted holes for anchoring to the ground.

### KIT CONTENTS

- 4 SEG9525 feet
- 4 M8 washers (available also in M10)
- 4 M8 TE screw (available also in M10)
- Installation guide



max.  
300 Kgs



CBSEG9525W/00

max.  
450 Kgs



CBSEG9525M/00

max.  
600 Kgs



CBSEG9525H/00


## GROUND ANCHORING



### INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes.
2. Fix the feet to the machine using screw and washers.
3. Anti-vibration feet installed correctly.





# NOCE6050 series

## DAMPER WITH CONTROLLED DEFLECTION

PATENTED elastomeric NOCE4040 series damper, designed with an elastic element defined as a connector which, when used between two containers, creates the condition to obtain anti-vibration devices with controlled deflection. This design prevents the vibration damper's deformation under load while insuring the perfect machine's insulation.




### AVAILABLE VERSIONS

Available in the following versions: nut-nut (NOCE6050DD), screw-nut (NOCE6050VD) or screw-screw (NOCE6050VV) depending on the anchoring needs.

### KIT CONTENTS


- 4 NOCE6050 feet
- M10 nuts (available also in M8/M12)
- M10 washers (available also in M8/M12)
- M10 TE screws (available also in M8/M12)
- Installation guide

### NOCE6050DD




SCREWS: 8 M10 washers - 8 M10 TE screws

### NOCE6050VD



SCREWS: 4 M10 nuts - 8 M10 washers - 4 M10 TE screws

### NOCE6050VV



SCREWS: 4 M10 nuts - 8 M10 washers

max.  
280 Kgs

max.  
360 Kgs

max.  
640 Kgs

max.  
1000 Kgs



CBNOCEVD6050V30M10L

CBNOCEVD6050V30M10W

CBNOCEVD6050V30M10M



CBNOCEVD6050V30M10H


ON WALL BRACKET  
ON GROUND BASE



## INSTALLATION INSTRUCTIONS

1. Place the feet in correspondence of the anchoring holes.
2. Fix the feet to the machine and to the bracket using screws, nuts and washers depending on your necessity.
3. Anti-vibration feet installed correctly.





# PNOCE6050V series



## DAMPER WITH CONTROLLED DEFLECTION

PATENTED elastomeric *NOCE4040* series damper, designed with an elastic element defined as a connector which, when used between two containers, creates the condition to obtain anti-vibration devices with controlled deflection. This design prevents the vibration damper's deformation under load while insuring the perfect machine's insulation.

Steel base plate with 2 cavities for anchoring the mount to the ground. The surface of the plates has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.

### KIT CONTENTS

- 4 PNOCE6050V feet
- 4 M10 nuts (available also in M8/M12)
- 4 M10 washers (available also in M8/M12)
- Allen key and Installation guide



max.  
280 Kgs



max.  
360 Kgs



max.  
640 Kgs



max.  
1000 Kgs



CBPNOCE6050V22M10L

CBPNOCE6050V22M10W

CBPNOCE6050V22M10M

CBPNOCE6050V22M10H

## GROUND ANCHORING



### INSTALLATION INSTRUCTIONS

1. Screw the plates to the bases of the anti-vibration feet with the screws and the allen wrench supplied.
2. Place the feet in correspondence of the anchoring holes.
3. Fix the feet to the machine and to the bracket using screws, nuts and washers depending on your necessity.

1.



2.



3.



# MCF series




## ELASTOMERIC DAMPER

Damper in THERMOPLASTIC ELASTOMER which has a high resistance to tearing, atmospheric aging, ozone, detergents, UV rays and also resists to temperatures from -45°C to +110°C.

The surface of the plate and the base has slip-proof, flexible embossing which allow the charged anti-vibration feet to stand by friction and at the same time reduce the transmission of noise.

### KIT CONTENTS

- 4 MCF feet
- 4 M10 nuts (available also in M8/M12)
- 4 M10 washers (available also in M8/M12)
- Installation guide









**ON THE  
GROUND**




## INSTALLATION INSTRUCTIONS


1. Place the feet in correspondence of the anchoring holes.
2. Fix the feet to the machine using nuts and washers.
3. Anti-vibration feet installed correctly.



**MNaZc - p. 3**



**NOCE4040 - p. 13**



## **COUNTER DISPLAY**


**Practical cardboard counter display with metal hooks.**

**Dimensions: 450x222x500 mm**

**Can fit 24 assorted kits of the *MNaZc* and the *NOCE4040* series to isolate machines up to 120 Kgs.**

**Blister kits are supplied with fixation screws and installation instructions.**



**Check out our user friendly guide to choose the most appropriate kit for your installation needs on page 2.**




SUITABLE FOR  
INSULATING MACHINES  
WITH WEIGHT UP TO  
120 KG



450x222x500 mm



*DISTRIBUTED BY*



**Soleco**  
engineering s.r.l.

[www.solecosrl.com](http://www.solecosrl.com) - [soleco@solecosrl.com](mailto:soleco@solecosrl.com)

via Masaccio 12, 20096 Pioltello (Mi) - Italy tel +39 02 92 44 311 - fax +39 02 73 96 50 50

cod.fisc. e p.IVA 01349290153 - reg. impr. MI 148283 M.9711244 - R.E.A. MI 835036